

# VEMCALL

## GUEST PAGING SYSTEM



|                     |                                 |
|---------------------|---------------------------------|
| Frequency Rate      | 433.05MHz~434.790MHz(434.75MHz) |
| Channel Spacing     | 25KHz                           |
| Spurious Rejection  | -60dB                           |
| Modulation Scheme   | FM(FSK)                         |
| Standard Deviation  | ± 4.5 KHz                       |
| Dimension (mm)      | W(170) X D(140) X H(425)        |
| Occupied Bandwidth  | 25 KHz                          |
| Total Weight        | 1.8Kg                           |
| BATTERY (Power)     | DC 12V 3.5A                     |
| Frequency Stability | ±10 ppm                         |
| Selectivity         | -108dBm                         |
| Certification       | CE, GOST-R                      |

- Durable and sturdy to withstand industry conditions
- Code Format : POCSAG Code
- Baud Rate - 512,1200 BPS
- Designed by VEMCALL in Denmark, Assembled in KOREA



|                     |                                |
|---------------------|--------------------------------|
| Frequency Rate      | RX : 433.92MHz, TX : 434.75MHz |
| Channel Spacing     | 25KHz                          |
| Spurious Rejection  | -60dB                          |
| Modulation Scheme   | FM(FSK)                        |
| Standard Deviation  | ± 4.5 KHz                      |
| Dimension (mm)      | W(13) X D(65) X H(65)          |
| Occupied Bandwidth  | 25 KHz                         |
| Total Weight        | 40g                            |
| BATTERY (Power)     | 3.7V Rechargeable              |
| Frequency Stability | ±10 ppm                        |
| Selectivity         | -108dBm                        |
| TX Power            | MAX 10mW                       |

Certification CE, GOST-R

- Code Format : POCSAG Code
- Data Rate - 1200 BPS
- Water resistant
- UHF Frequency
- Alert : Vibe, Buzzer, LED & FND
- Low battery melody
- Out of range
- Designed by VEMCALL in Denmark, Assembled in KOREA



|                     |                     |
|---------------------|---------------------|
| Frequency Rate      | 433.05MHz~434.79MHz |
| Channel Spacing     | 12.5KHz             |
| Spurious Rejection  | -60dB               |
| Modulation Scheme   | F1D(FSK, Data)      |
| Number of Channels  | 10 channel          |
| Standard Deviation  | ± 4.5 KHz           |
| Dimension (mm)      | 215 x 215 x 25      |
| Occupied Bandwidth  | ±8.5 KHz            |
| Total Weight        | 450g                |
| BATTERY (Power)     | DC 12V 3.5A         |
| Frequency Stability | ±2.5 ppm            |
| Temperature range   | -20°C ~ 50°C        |
| Power               | 10mW(+10dBm)        |
| Certification       | CE, GOST-R          |

- Built-in Clock
- Wireless Pager Programmability
- Durable and sturdy to withstand industry conditions
- Auto Locate • Out of Range
- Code Format : POCSAG Code
- Baud Rate - 512,1200 BPS